

Declaration of Performance

No. 01/2024/ ART

1. Unique product ID: **ACG/2014**
2. Indented application: **Used to provide natural lighting, ventilation and exits to the roof for residential and non-residential buildings. Installation is suitable for flat or slightly sloped roofs.**
3. Manufacturer: **Artus, s.r.o., Křížíkova 2413, 256 01 Benešov, Business ID: 25793985**
4. Entrusted subject: **not relevant**
5. POSV system/systems: **system 3**
- 6a. Harmonized standard: **EN 1873:2005**

Notified bodies: **Technical and Test Institute for Construction in Prague, s.o., subsidiary 0100 Prague**, Prosecká 811/76a, 190 00 Praha 9, Czech Republic, no. 1020 issued the declaration protocol no. 1020 – CPR – 010039533 dated 28 Feb 2018.
PAVUS, a.s., subsidiary Veselí nad Lužnicí, Prosecká 412/74, 190 00 Praha 9 issued the flame reaction classification protocol no. PK1-01-19-048-C-0 dated 28 Aug 2019.

7. Declared property / declared properties:

Basic characteristics	Properties	Harmonized technical specifications	
Mechanical endurance:			
- upward load	UL 3000	EN 1873:2005	
- downward load	DL 2500 (without cover dome) DL 1125 (with cover dome)		
Reaction to flame:	See Annex 1		
Fire resistance:	NPD		
Behaviour in case of external fire:	NPD		
Water resistance:			
- Skylight with a stand	Passed		
- Light-permeant part of the skylight	Passed		
Shock resistance:			
- Hard body of small dimensions	Passed		
- Soft body of large dimensions	SB 1200		
Air sound proofing:	Depends on type of filling (see Annex 1)		
Heat transfer:	(See Annex 1)		
Transmittance	Depends on type of filling (see Annex 1)		
Air tightness:	Class 2		
Shelf life:			
- Change of overall light transmittance	NPD		
- Yellow index change	NPD		
- Change of mechanical properties	NPD		

8. Associated technical documentation: **not relevant**

The properties of the above-stated product complies with the set of declared properties. This declaration of performance is in compliance with Regulation (EU) No. 305/2011 issued on the exclusive liability of the above-stated manufacturer.

Signed for and in behalf of the producer:

In Benešov, dated 15 Feb 2024

Daniel Artus – representative

Declaration of Performance No. 01/2024/ ART– Annex 1

Product:


ARTUS point roof skylight – Composite Glass (ACG)

Basic characteristics	Properties
Reaction to fire	Class E
Heat transfer coefficient with upstand Heat transfer coefficient without upstand - Skylight with glazing – four-layer dome - Skylight with glazing – three-layer dome - Skylight with glazing – two-layer dome - Skylight with glazing – Insulating layered triple glass - Skylight with glazing – Insulating layered triple glass + cover dome - Skylight with glazing – insulating layered double glass - Skylight with glazing – PC sheet 16 mm thick + cover dome - Skylight with glazing – PC sheet 25 mm thick + cover dome - Skylight with glazing – PC sheet 32 mm thick + cover dome - Skylight with glazing – PC sheet 16 mm thick - Skylight with glazing – PC sheet 25 mm thick - Skylight with glazing – PC sheet 32 mm thick Heat transfer coefficient of the upstand - PVC upstand – splayed upstand with PUR insulation - PVC upstand – vertical upstand with PUR insulation - laminate upstand with PUR insulation - steel upstand with ORSIL insulation	NPD $U_g=1,31 \text{ W/m}^2\text{K}$, $U_w=1,30 \text{ W/m}^2\text{K}$ $U_g=1,75 \text{ W/m}^2\text{K}$, $U_w=1,64 \text{ W/m}^2\text{K}$ $U_g=2,64 \text{ W/m}^2\text{K}$, $U_w=2,32 \text{ W/m}^2\text{K}$ $U_g=0,70 \text{ W/m}^2\text{K}$, $U_w=0,95 \text{ W/m}^2\text{K}$ $U_g=0,63 \text{ W/m}^2\text{K}$, $U_w=0,90 \text{ W/m}^2\text{K}$ $U_g=1,10 \text{ W/m}^2\text{K}$, $U_w=1,26 \text{ W/m}^2\text{K}$ $U_g=1,40 \text{ W/m}^2\text{K}$, $U_w=1,37 \text{ W/m}^2\text{K}$ $U_g=1,10 \text{ W/m}^2\text{K}$, $U_w=1,14 \text{ W/m}^2\text{K}$ $U_g=0,90 \text{ W/m}^2\text{K}$, $U_w=0,98 \text{ W/m}^2\text{K}$ $U_g=1,82 \text{ W/m}^2\text{K}$, $U_w=1,69 \text{ W/m}^2\text{K}$ $U_g=1,30 \text{ W/m}^2\text{K}$, $U_w=1,29 \text{ W/m}^2\text{K}$ $U_g=1,10 \text{ W/m}^2\text{K}$, $U_w=1,14 \text{ W/m}^2\text{K}$ Declared parameters according to ČSN EN ISO 6946 $U_p = 0,88 \text{ W/(m}^2\text{K)}^*$ $U_p = 0,92 \text{ W/(m}^2\text{K)}^*$ $U_p = 0,88 \text{ W/(m}^2\text{K)}^*$ $U_p = 0,96 \text{ W/(m}^2\text{K)}^*$
Air sound proofing - Skylight with glazing – insulating layered double glass + cover dome - Skylight with glazing – four-layer dome - Skylight with glazing – PC sheet 25 mm thick + cover dome	$R_w=31 \text{ dB}$ $R_w=25 \text{ dB}$ $R_w=25 \text{ dB}$
Air permeability - Skylight with glazing – PC sheet 25 mm thick with no cover dome - Skylight with glazing – two-to-four-layer dome	Class 2
Water tightness - Skylight with glazing – PC sheet 25 mm thick with and without cover dome - Skylight with glazing – two-to-four-layer dome	Passed
Upward load - Skylight with glazing – PC sheet with and without cover dome - Skylight with glazing – layered glass with and without cover dome - Skylight with glazing – two-to-four-layer dome	UL 3000
Downward load - Skylight with glazing – PC sheet without cover dome - Skylight with glazing – PC sheet with cover dome - Skylight with glazing – layered glass without cover dome - Skylight with glazing – layered glass with cover dome - Skylight with glazing – two-to-four-layer dome	$DL 2500$ $DL 1125$ $DL 2500$ $DL 1125$ $DL 2500$
Hard body impact - Skylight with glazing – PC sheet with and without cover dome - Skylight with glazing – layered glass with and without cover dome - Skylight with glazing – two/three/four-layer dome	No damage
Soft body impact - Skylight with glazing – PC sheet with and without cover dome - Skylight with glazing – layered glass with and without cover dome - Skylight with glazing – two-to-four-layer dome - Skylight with glazing – one-layer Plexiglas Ressit SG dome	SB 1200
Light transmittance - PMMA dome glazing – one-layer, clear - PMMA dome glazing – one-layer, opal - PMMA dome glazing – two/three/four-layer clear dome - PMMA dome glazing – two/three/four-layer opal dome - Glazing Insulating layered triple glass - Glazing Insulating layered double glass	93% 89% $80\%, 75\%, 70\%$ $75\%, 70\%, 65\%$ 61% $71-72\%$

Signed for and in behalf of the producer:

In Benešov, dated 15 Feb 2024

Daniel Artus – representative



Annex 2: CE marking

ARTUS point roof skylight – Composite Glass (ACG) without upstand



18

Artus, s.r.o., Křižíkova 2413, 256 01 Benešov, Business ID: 25793985

EN 1873:2005

Declaration of Performance No. 01/2024/ ART – see www.svetlikyartus.cz

ACG/2014

Point roof skylight without stand, used to provide natural lighting, ventilation and exits to the roof for residential and non-residential buildings. Installation is suitable for flat or slightly sloped roofs.

Mechanical endurance:

- upward load

UL 3000

- downward load

DL 2500 (without cover dome)
DL 1125 (with cover dome)

Reaction to fire:

Class E

Fire resistance:

NPD

Behaviour in case of external fire:

NPD

Water resistance:

- Skylight with a stand

Passed

- Light-permeant part of the skylight

Passed

Shock resistance:

- Hard body of small dimensions

Passed

- Soft body of large dimensions

SB 1200

Air sound proofing:

Depends on type of filling- see Annex 1

Heat transfer coefficient:

- Light-permeant part of the skylight

Depends on type of filling- see Annex 1

Transmittance

Depends on type of filling- see Annex 1

Air tightness:

- Skylight with a stand

Class 2

- Light-permeant part of the skylight

Passed

Shelf life:

- Change of overall light transmittance

NPD

- Yellow index change

NPD

- Changes in mechanical properties

NPD

Signed for and in behalf of the manufacturer:

In Benešov, dated 15 Feb 2024

Declaration of Product Performance for ACG/2014, no. 01/2024/ART

Daniel Artus – representative

3/4

**ARTUS point roof skylight – Composite Glass (ACG)
with PVC or laminate upstand**



18

Artus, s.r.o., Křižíkova 2413, 256 01 Benešov, Business ID: 25793985

EN 1873:2005

Declaration of Performance No. 01/2024/ ART – see www.svetlikyartus.cz

ACG/2014

Point roof skylight with stand, used to provide natural lighting, ventilation and exits to the roof for residential and non-residential buildings. Installation is suitable for flat or slightly sloped roofs.

Mechanical endurance:

- upward load	UL 3000
---------------	---------

- downward load	DL 2500 (without cover dome) DL 1125 (with cover dome)
-----------------	---

Reaction to fire:	Class E
--------------------------	---------

Fire resistance:	NPD
-------------------------	-----

Behaviour in case of external fire:	NPD
--	-----

Water resistance:

- Skylight with a stand	Passed
-------------------------	--------

- Light-permeant part of the skylight	Passed
---------------------------------------	--------

Shock resistance:

- Hard body of small dimensions	Passed
---------------------------------	--------

- Soft body of large dimensions	SB 1200
---------------------------------	---------

Air sound proofing:	Depends on type of filling- see Annex 1
----------------------------	---

Heat transfer coefficient:

- Light-permeant part of the skylight	Depends on type of filling- see Annex 1
---------------------------------------	---

Transmittance	Depends on type of filling- see Annex 1
----------------------	---

Air tightness:

- Skylight with a stand	Class 2
-------------------------	---------

- Light-permeant part of the skylight	Passed
---------------------------------------	--------

Shelf life:

- Change of overall light transmittance	NPD
---	-----

- Yellow index change	NPD
-----------------------	-----

- Changes in mechanical properties	NPD
------------------------------------	-----

Signed for and in behalf of the manufacturer:

In Benešov, dated 15 Feb 2024

Daniel Artus – representative